

SAFETY DATA SHEET **CENTRI ACTIVATORS**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CENTRI ACTIVATORS

Product number 2357

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Activator.

1.3. Details of the supplier of the safety data sheet

WHW Plastics Ltd Supplier

> Therm Road Cleveland Street

Hull

East Yorkshire HU8 7BF

1.4. Emergency telephone number

Emergency telephone +44(0)1482 329154 (Office hours Only)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Aerosol 1 - H222, H229

Health hazards Skin Irrit. 2 - H315 STOT SE 3 - H336

Environmental hazards Aquatic Chronic 2 - H411

1999/45/EC)

Classification (67/548/EEC or F+; R12. Xi; R38. N; R51/53. R67

Human health Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional

information on health hazards.

Environmental The product contains a substance which is toxic to aquatic organisms.

Physicochemical Containers can burst violently or explode when heated, due to excessive pressure build-up.

The product is extremely flammable. Vapours may form explosive mixtures with air.

2.2. Label elements

Pictogram







Signal word

Danger

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Revision date: 20/01/2016 Revision: 2 Supersedes date: 30/07/2014

CENTRI ACTIVATORS

P102 Keep out of reach of children. Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing vapour/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Contains HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE,

> HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE P264 Wash contaminated skin thoroughly after handling.

Supplementary precautionary

statements

P273 Avoid release to the environment.

P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with national regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

HYDROCARBONS	S, C6-C7, N-ALKANES, ISOALKANES,	30-60%
--------------	----------------------------------	--------

CYCLICS, <5% N-HEXANE

CAS number: 64742-49-0 EC number: 921-024-6 REACH registration number: 01-

2119475514-35-XXXX

Classification

Flam. Liq. 2 - H225

Skin Irrit. 2 - H315

STOT SE 3 - H336

Asp. Tox. 1 - H304

STOT SE 3 - H336

Aquatic Chronic 2 - H411

PETROLEUM GASES, LIQUEFIED

10-30%

CAS number: 68476-85-7 EC number: 270-704-2

Classification

Flam. Gas 1 - H220

Press. Gas, Compressed - H280

Revision date: 20/01/2016 Revision: 2 Supersedes date: 30/07/2014

CENTRI ACTIVATORS

HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE

CAS number: 64742-49-0 EC number: 931-254-9 REACH registration number: 01-

2119484651-34-XXXX

10-30%

Classification

Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

N,N-DIMETHYL-P-TOLUIDINE <1%

CAS number: 99-97-8 EC number: 202-805-4

Classification

Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT RE 2 - H373

Aquatic Chronic 3 - H412

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Get medical attention if any discomfort continues.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. If in doubt, get medical attention promptly.

Ingestion Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for

breathing. Get medical attention.

Skin contact Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur

after washing.

Eye contact Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of

water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms

occur after washing.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Revision date: 20/01/2016 Revision: 2 Supersedes date: 30/07/2014

CENTRI ACTIVATORS

Specific hazards

Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during

firefighting

Use water to keep fire exposed containers cool and disperse vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without

risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory

protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near

spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into

containers.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards. See Section 12 for additional information on ecological hazards. For waste disposal,

see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Read and follow manufacturer's

recommendations. When sprayed on a naked flame or any incandescent material the aerosol

vapours can be ignited. Use suitable respiratory protection if ventilation is inadequate.

Advice on general

occupational hygiene

Wash promptly with soap and water if skin becomes contaminated. Do not eat, drink or smoke

when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Protect from freezing and direct sunlight. Store in a dry place. Do not store near heat sources

or expose to high temperatures. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

PETROLEUM GASES, LIQUEFIED

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³ Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

WEL = Workplace Exposure Limit

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE (CAS: 64742-49-0)

CENTRI ACTIVATORS

DNEL Consumer - Oral; Long term systemic effects: 699 mg/kg/day

Workers - Oral; Long term systemic effects: 773 mg/kg/day Workers - Dermal; Long term systemic effects: 773 mg/kg/day Consumer - Dermal; Long term systemic effects: 699 mg/kg/day Consumer - Inhalation; Long term systemic effects: 608 mg/m³

HYDROCARBONS, C6 ISOALKANES < 5% N-HEXANE (CAS: 64742-49-0)

DNEL Consumer - Oral; Long term systemic effects: 1301 mg/kg/day

Consumer - Dermal; Long term systemic effects: 1377 mg/kg/day Workers - Dermal; Long term systemic effects: 13964 mg/kg/day Consumer - Inhalation; Long term systemic effects: 1131 mg/m³ Workers - Inhalation; Long term systemic effects: 5306 mg/m³

8.2. Exposure controls

eye contact is possible.

Hand protection

No specific requirements are anticipated under normal conditions of use.

Other skin and body

protection

Wear suitable protective equipment for prolonged exposure and/or high concentrations of

vapours, spray or mist.

Respiratory protection No specific recommendations. If ventilation is inadequate, suitable respiratory protection must

be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Clear.

Odour Solvents

Odour threshold No information available.

pH No information available.

Melting point No information available.

Initial boiling point and range -41 (-41 TO 215)°C @

Flash point -40°C CC (Closed cup).

Evaporation rate No information available.

Evaporation factor No information available.

Flammability (solid, gas) Upper/lower flammability or

as) No information available.

explosive limits

Lower flammable/explosive limit: 1.0 % Upper flammable/explosive limit: 9.5 %

Vapour pressure No information available.

Vapour density No information available.

Relative density 0.651

Solubility(ies) Insoluble in water. Partition

coefficient No information available.

Revision date: 20/01/2016 Revision: 2 Supersedes date: 30/07/2014

CENTRI ACTIVATORS

Auto-ignition temperature 413°C

Decomposition Temperature No information available.

Viscosity No information available.

Explosive properties No information available.

No information available. Oxidising properties

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability The product may not be stable under some conditions of storage or use.

10.3. Possibility of hazardous reactions

Possibility of hazardous

None known.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high

temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid None known.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None at ambient temperatures.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 25,000.0

Acute toxicity - dermal

ATE dermal (mg/kg) 75,000.0

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 750.0

Inhalation Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness

and nausea.

Skin contact Causes skin irritation.

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic health

No known chronic or acute health risks.

hazards

CENTRI ACTIVATORS

Route of entry Skin and/or eye contact Inhalation

Toxicological information on ingredients.

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

5,001.0

Species Rat

ATE oral (mg/kg) 5,001.0

Acute toxicity - dermal

Acute toxicity dermal (LD50 2,001.0

mg/kg)

Species Rabbit

ATE dermal (mg/kg) 2,001.0

HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

5,001.0

Species Rat

ATE oral (mg/kg) 5,001.0

Acute toxicity - dermal

Acute toxicity dermal (LD50 2,001.0

mg/kg)

, - - -

Species Rabbit

ATE dermal (mg/kg) 2,001.0

Acute toxicity - inhalation

Acute toxicity inhalation

(LC₅₀ vapours mg/l)

21.0

Species Rat

ATE inhalation (vapours

mg/l)

21.0

N,N-DIMETHYL-P-TOLUIDINE

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

1,650.0

Species Rat

ATE oral (mg/kg) 100.0

Acute toxicity - inhalation

Revision date: 20/01/2016 Supersedes date: 30/07/2014 Revision: 2

CENTRI ACTIVATORS

Acute toxicity inhalation 1.4

(LC50 vapours mg/l)

Species Rat 3.0

ATE inhalation (vapours

mg/l)

SECTION 12: Ecological Information

12.1. Toxicity

Ecological information on ingredients.

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE

Acute toxicity - fish LOEC, : 1-10 mg/l, Fish Acute toxicity - aquatic LOEC, : 10-100 mg/l, Algae

plants

Acute toxicity -LOEC, : 1-10 mg/l, Activated sludge

microorganisms

HYDROCARBONS, C6 ISOALKANES < 5% N-HEXANE

Acute toxicity - fish LOEC, : 10-100 mg/l, Fish Acute toxicity - aquatic LOEC, : 10-100 mg/l, Algae

plants

N,N-DIMETHYL-P-TOLUIDINE

Acute toxicity - fish LC₅₀, 96 hours: 46-52 mg/l, Pimephales promelas (Fat-head Minnow)

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Partition coefficient No information available.

12.4. Mobility in soil

Mobility No data available

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB This product does not contain any substances classified as PBT or vPvB.

assessment

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

Disposal methods Containers should be thoroughly emptied before disposal because of the risk of an explosion.

Do not pierce or burn, even after use.

CENTRI ACTIVATORS

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name

AEROSOLS

(ADR/RID)

Proper shipping name

AEROSOLS

(IMDG)

Proper shipping name (ICAO) AEROSOLS, FLAMMABLE

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

Revision date: 20/01/2016 Revision: 2 Supersedes date: 30/07/2014

CENTRI ACTIVATORS

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Council Directive of 20 May 1975 on the approximation of the laws of the Member States

relating to aerosol dispensers (75/324/EEC) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 20/01/2016

Revision 2

Supersedes date 30/07/2014

SDS number 4864

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H229 Pressurised container: may burst if heated

H280 Contains gas under pressure; may explode if heated.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.