

Revision: 20.07.2017

Printing date 20.07.2017

Version number 3

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: FotoDent setup 385nm / 405 nm
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture

Material based on methacrylate resin for DLP-systems with 385 nm / 405 nm LED for manufacturing of dental models

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Dreve Dentamid GmbH Max-Planck-Straße 31 59423 Unna / Germany Tel.: ++49 2303 /8807-0

Fax.: ++49 2303 / 8807-55

· Further information obtainable from:

Department Research & Development

Fax: ++49 2303 / 8807-562

Email: sicherheitsdatenblatt@dreve.de · 1.4 Emergency telephone number:

Tel.: ++ 49 211 / 797-3350 Plant Fire Department Henkel

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



H317 May cause an allergic skin reaction. Skin Sens. 1

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:
- 2-Propenoic acid, reaction product with Pentaerythrite
- 1,4 Butanediol dimethacrylate

(Contd. on page 2)



Printing date 20.07.2017 Version number 3 Revision: 20.07.2017

Trade name: FotoDent setup 385nm / 405 nm

(Contd. of page 1)

phenyl bis(2,4,6-trimethylbenzoyl)-phosphineoxide

Pigments

· Hazard statements

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous componer | nts: | |
|----------------------|--|---------|
| CAS: 41637-38-1 | Ethoxylated (04) Bisphenol A Dimethacrylate | 50-100% |
| EC number: 609-946-4 | Aquatic Chronic 4, H413 | |
| | Acrylic resin | 10-25% |
| | | |
| CAS: 2082-81-7 | 1,4 Butanediol dimethacrylate | 2.5-10% |
| EINECS: 212-218-1 | ♦ Skin Sens. 1, H317 | |
| | 2-Propenoic acid, reaction product with Pentaerythrite | 2.5-10% |
| EC number: 629-850-6 | Eye Dam. 1, H318; 🍫 Aquatic Chronic 2, H411; 🗘 Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 | |
| CAS: 162881-26-7 | phenyl bis(2,4,6-trimethylbenzoyl)-phosphineoxide | ≤ 2.5% |
| ELINCS: 423-340-5 | 🕠 Skin Sens. 1, H317; Aquatic Chronic 4, H413 | |
| | Pigments | ≤ 2.5% |
| | 💠 Eye Irrit. 2, H319; Skin Sens. 1, H317 | |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)



Printing date 20.07.2017 Version number 3 Revision: 20.07.2017

Trade name: FotoDent setup 385nm / 405 nm

(Contd. of page 2)

· After swallowing:

Do not induce vomiting.

Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Avoid contact with skin and eyes.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Protect from heat and direct sunlight.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

GB



Printing date 20.07.2017 Version number 3 Revision: 20.07.2017

Trade name: FotoDent setup 385nm / 405 nm

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

Protective gloves should be changed regularly, especially after intensive contact with the product. For every workplace a suitable type of protective gloves must be selected.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR (0,4 mm)

As there are many different conditions in every day work these indications can only serve as an aid to orientation for the selection of suitable gloves for the handling of chemical products. By no means they can replace qualifying examinations by the end-user.

These recommendations only apply to the product mentioned in the safety data sheet. When mixing with other substances or under conditions deviant from norm EN 374 a manufacturer of CE-approved gloves should be referred to.


The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· Eye protection:



(Contd. on page 5)



Printing date 20.07.2017 Version number 3 Revision: 20.07.2017

Trade name: FotoDent setup 385nm / 405 nm

(Contd. of page 4)

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid Yellow

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: >100 °C

· Flash point: 91 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 200 °C

· Decomposition temperature: Not determined.

• Auto-ignition temperature: Product is not selfigniting.

• **Explosive properties:** Product does not present an explosion hazard.

Not miscible or difficult to mix.

· Explosion limits:

Lower: Not determined.
Upper: Not determined.
Oxidising properties Not determined

Vapour pressure: Not determined.

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

Evaporation rate Not determined. Solubility in / Miscibility with

Date to the state of the state

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined. Kinematic: Not determined.

· Solvent content:

Organic solvents: 0.0 %

• **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No dangerous reactions if used according to specifications.
- · 10.2 Chemical stability Stable if used according to specifications.

(Contd. on page 6)



Printing date 20.07.2017 Version number 3 Revision: 20.07.2017

Trade name: FotoDent setup 385nm / 405 nm

(Contd. of page 5)

· Thermal decomposition / conditions to be avoided:

Protect from heat and direct sunlight.

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC50 v | alues rele | evant for classification: |
|-------------|------------------------|---|
| 1245638-6 | 1-2 2-Pro _l | penoic acid, reaction product with Pentaerythrite |
| Oral | LD50 | >2000 mg/kg (rat) |
| Dermal | LD50 | >2000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >5 mg/l (rat) |

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.

(Contd. on page 7)



Printing date 20.07.2017 Version number 3 Revision: 20.07.2017

Trade name: FotoDent setup 385nm / 405 nm

(Contd. of page 6)

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue

HP 14 Ecotoxic

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| | ion | |
|--|-----------------|--|
| · 14.1 UN-Number | V.·· | |
| · ADR, ADN, IMDG, IATA | Void | |
| · 14.2 UN proper shipping name | | |
| · ADR, ADN, IMDG, IATA | Void | |
| · 14.3 Transport hazard class(es) | | |
| · ADR, ADN, IMDG, IATA | | |
| · Class | Void | |
| · 14.4 Packing group | | |
| · ADR, IMDG, IATA | Void | |
| · 14.5 Environmental hazards: | Not applicable. | |
| · 14.6 Special precautions for user | Not applicable. | |
| · 14.7 Transport in bulk according to An | nex II | |
| of Marpol and the IBC Code | Not applicable. | |
| · UN "Model Regulation": | Void | |

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 8)



Printing date 20.07.2017 Version number 3 Revision: 20.07.2017

Trade name: FotoDent setup 385nm / 405 nm

(Contd. of page 7)

· Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

· Department issuing SDS: Department Research & Development

· Contact: Dr. Thomas Veit, Lothar Sutor, Susanne Langesberg

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

· * Data compared to the previous version altered.

GB