

## SAFETY DATA SHEET

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name Description HEAT CURE - POLY(MMA) BASED Product Product

Polymer based on Methyl methacrylate containing peroxide.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s)

Manufacture of dental and medical products.

Manufacture of porous moulds.

Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

WHW Plastics Ltd, Therm Road, Cleveland Street, Hull, East Yorkshire HU8 7BF, UK

Tel: +44(0)1482 329154 sales@whwplastics.com

1.4 Emergency telephone number

+44(0)1482 329154

# 2. SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

This product does not meet the criteria for classification in any hazard class according to UK Regulations on classification, labelling and packaging of substances and mixtures.

2.2 Label elements

EUH208: Contains: (Methyl methacrylate, Dibenzoyl peroxide). May produce an

allergic reaction.

EUH210: Safety data sheet available on request.

2.3 Other hazards

Not classified as PBT or vPvB. Combustible but not readily ignited. May form combustible dust concentrations in air. Low toxicity under normal conditions of handling and use. Does not cause endocrine disruption.

## 3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.1 Substances

### 3.2 Mixtures

Substances in the mixture are not classified or are below required disclosure limits.

## 4. SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Skin Contact

IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Molten material can cause severe burns. Do NOT try to peel molten polymer from the skin. Cool

rapidly with water.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

Ingestion

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Obtain medical attention if ill effects occur.

## 4.2 Most important symptoms and effects, both acute and delayed

Not applicable.

#### 4.3 Indication of any immediate medical attention and special treatment needed

None necessary.

## SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media

Suitable Extinguishing Media Water spray, foam, dry powder or CO<sub>2</sub>.

Unsuitable extinguishing media Do not use water jet.

#### 5.2 Special hazards arising from the substance or mixture

Combustible but not readily ignited. May form combustible dust concentrations in air. The minimum ignition temperature of a dust cloud of a similar polymer has been measured at approximately 480°C (IEC 1241-2-1). Combustion or thermal decomposition will evolve toxic, irritant and flammable vapours.

#### 5.3 Advice for firefighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions.

## 6. SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Caution - spillages may be slippery.

#### 6.2 Environmental precautions

Avoid release to the environment.

### 6.3 Methods and material for containment and cleaning up

Collect in containers for disposal using approved dust respirator.

### 6.4 Reference to other sections

See section: 8, 13

## 7. SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Do not eat, drink or smoke at the workplace. Product as supplied: Avoid contact with skin and eyes. Unlikely to represent a dust hazard under normal handling conditions.

Dental resins are usually processed in conjunction with reactive monomers and this may require the use of a higher level of PPE than that necessary for the polymer itself. Please also see the advice in Sections 8 and 11. The following constitutes general advice: Extra care should be taken to prevent burns from contact with hot material. Thermal processing requires adequate ventilation to remove any monomer decomposition products, and use of inert atmosphere may be required in some processes to safely decompose the resin when it is used as a binder. Any thermal processing must consider the time-temperature decomposition of the resin. All polymers degrade to some extent at their processing temperature, an effect which increases with increasing temperature. It is therefore impossible to be precise about which substances may be evolved. However, it is only the minor components which vary substantially. The major components are given in Section 10. If the product is to be used in applications for which the hazards are not fully understood it is recommended to consult the supplier before use.

#### 7.2 Conditions for safe storage, including any incompatibilities

Acrylic polymers are supplied in either bags or bulk containers. Keep containers in a clean, cool and dry area away from heat sources. Natural ventilation is adequate.

Storage temperature (°C): Preferably not exceeding 40°C.

Incompatible materials: Polymer contains residual benzoyl peroxide. This may react with oxidising agents, reducing

agents, acids, bases and amines leading to decomposition.

#### 7.3 Specific end use(s)

Manufacture of dental and medical products.

Manufacture of porous moulds.

## 8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

Substance	CAS No.	LTEL ppm	LTEL mg/m³	STEL	STEL	Notes
		(8Hr TWA)	(8Hr TWA)	ppm	mg/m³	
Dust (total inhalable dust)			10			WEL
(respirable dust)			4			
Dibenzoyl peroxide	000094-36-0		5			WEL
Traces of: Aluminium oxides	001344-28-1					WEL
total inhalable dust			10			
respirable dust			4			
The following values apply to						
substances which may be evolved						
during thermal processing.						
Methyl methacrylate	000080-62-6	50	208	100	416	WEL

### 8.2 Exposure controls

Appropriate engineering controls

Do not eat, drink or smoke at the workplace. Provide adequate ventilation, including appropriate local extraction, to ensure that the occupational exposure limit is not exceeded. Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required. The following information is given as general guidance.

Individual protection measures, such as personal protective equipment (PPE) Eye/face protection



Wear eye/face protection. Safety spectacles/goggles/full face shield.

#### Skin protection



Wear suitable gloves.

Suitable materials: Butyl; EN 374.

Suitability of gloves should be confirmed with glove manufacturer. Change gloves, if contamination occurs or duration of activity exceeds breakthrough time. Breakthrough time of the glove material: refer to the information provided by the gloves' producer.

#### Respiratory protection



A suitable dust mask or dust respirator with filter type P3 or FFP3 (EN143 or EN149) may be appropriate. In the unlikely event of formation of particularly high levels of dust a self contained breathing apparatus may be appropriate.

#### Thermal hazards

Wear thermal insulating gloves when handling hot masses.

Wear suitable respiratory protective equipment if exposure to levels above the occupational exposure limit is likely. A suitable mask with filter type A (EN141 or EN405) may be appropriate. In the unlikely event of formation of particularly high levels of vapour a self contained breathing apparatus may be appropriate.

## 9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties

Appearance Fine beads.

White.
Odour Typically methacrylate.

Odour Threshold (ppm)

PH

Not available.

Not available.

Melting Range (°C)

150 - 230

Melting Range (°C) 150 - 230

Boiling Point (°C) Not applicable.

Flash Point (°C) Not applicable.

Relative Evaporation Rate (Ether = 1) Not applicable.

Flammability (solid, gas) Not applicable.

Revision: CLP2 CENTRI-BASE HEAT CURE - POLY(MMA) BASED

Flammable Limits Not applicable. Vapour pressure (Pascal) Not applicable. Vapour Density (Air=1) Not applicable. Density (g/ml) 1.1 - 1.18 Bulk Density (g/ml) 0.60 - 0.70 Solubility (Water) Negligible. Solubility (Other) Not available. Partition Coefficient (n-Octanol/water) Not applicable. Auto Ignition Temperature (°C) Not applicable. Decomposition Temperature (°C) Not available.

Kinematic Viscosity (mm²/s)

Explosive properties

Not applicable.

Weakly to moderately explosible.

Oxidising properties Not applicable.

9.2 Other information

Viscosity (mPa. s)

Particle characteristics Not available.

St Class 1

## 10. SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity

Non-reactive material.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

None known.

#### 10.4 Conditions to avoid

Avoid dust generation. Keep away from heat.

### 10.5 Incompatible materials

Polymer contains residual benzoyl peroxide. This may react with oxidising agents, reducing agents, acids, bases and amines leading to decomposition.

Not applicable.

### 10.6 Hazardous decomposition products

Methyl methacrylate, Dibenzoyl peroxide, Carbon dioxide, Carbon monoxide.

## 11. SECTION 11: TOXICOLOGICAL INFORMATION

## 11.1 Information on toxicological effects

Acute toxicity

Ingestion Based upon the available data, the classification criteria are not met.

Low oral toxicity.

Inhalation Based upon the available data, the classification criteria are not met.

High concentrations of dust may be irritant to the respiratory tract. High

concentrations of vapour from hot operations may be harmful, cause irritation of the

respiratory tract and slight narcotic effects.

Skin corrosion/irritation

Based upon the available data, the classification criteria are not met.

Serious eye damage/irritation

Based upon the available data, the classification criteria are not met.

Dust may cause irritation.

Sensitisation It is not a skin sensitiser. (By analogy with similar materials)

Contains: (Methyl methacrylate, Dibenzoyl peroxide). During normal handling this will not constitute a hazard. If the polymer matrix is destroyed e.g. when the product is dissolved in organic solvent, chemical residues will be released from the polymer matrix. Under these conditions, they may produce an allergic reaction in persons

already sensitised.

Carcinogenicity Based upon the available data, the classification criteria are not met.

Germ cell mutagenicity Reproductive toxicity Based upon the available data, the classification criteria are not met. Based upon the available data, the classification criteria are not met.

STOT - single exposure STOT - repeated exposure Based upon the available data, the classification criteria are not met.

Based upon the available data, the classification criteria are not met.

Aspiration hazard

Based upon the available data, the classification criteria are not met.

## 12. SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

The product is predicted to have low toxicity to aquatic organisms.

### 12.2 Persistence and degradability

The product is non-biodegradable in soil. There is no evidence of degradation in soil and water.

#### 12.3 Bioaccumulative potential

The product has low potential for bioaccumulation.

### 12.4 Mobility in soil

The product is predicted to have low mobility in soil.

### 12.5 Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

### 12.6 Other adverse effects

None known.

### 13. SECTION 13: DISPOSAL CONSIDERATIONS

The waste is considered to be non hazardous. Clean scrap may be reprocessed. Certain packages are returnable. Please consult your local office for further details. Ensure that all packaging is disposed of safely.

#### 13.1 Waste treatment methods

May be disposed of by landfill in accordance with local regulations. Incineration may be used to recover energy value. Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

## 14. SECTION 14: TRANSPORT INFORMATION

## 14.1 UN number

Not applicable.

### 14.2 UN Proper Shipping Name

Not applicable.

### 14.3 Transport hazard class(es)

Not applicable.

## 14.4 Packing group

Not applicable.

### 14.5 Environmental hazards

Not applicable.

### 14.6 Special precautions for user

Not applicable.

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

## 15. SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567 EH40/2005 Workplace exposure limits

#### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out for this substance/mixture. Not required.

### SECTION 16: OTHER INFORMATION

This Safety Data Sheet was prepared in accordance with REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 and SI 2020/1577.

The following sections contain revisions or new

1, 7

statements:

Date of preparation:

13 -June- 2023

#### **LEGEND**

Note: Not all of the following are necessarily contained in this Safety Data Sheet:

IOELV: Indicative Occupational Exposure Limit Value WEL: Workplace Exposure Limit (UK HSE EH40) Bmgv: Biological Monitoring Guidance Value Sen: Capable of causing respiratory sensitisation

Sk: Can be absorbed through skin

Carc: Capable of causing cancer and/or heritable genetic damage

CHAN: Chemical Hazard Alert Notice

COM: The company aims to control exposure in its workplace to this limit

LTEL: Long Term Exposure Limit STEL: Short Term Exposure Limit TWA: Time Weighted Average

PNEC: Predicted No-Effect Concentration

DNEL: Derived No-Effect Level STOT: Specific Target Organ Toxicity

Repr.: Reproductive toxicity

Aquatic acute/chronic: Hazardous to the aquatic environment

#### IMPORTANT: USE IN THE MANUFACTURE OF MEDICAL DEVICES AND RELATED PRODUCTS.

WHW Plastics Ltd has performed no clinical testing on the use of this product in any medical application. WHW Plastics Ltd Limited has no data to support the use of this product in any medical application. This product has been manufactured to a specification according to high standards of manufacturing practice. WHW Plastics Ltd supplies this product on the specific understanding that it is the sole responsibility of the medical device manufacture to ensure that the medical device is both safe and fit for the intended purpose and that this product is suitable for use in its manufacture.

It is the responsibility of the end-product manufacturer to identify all market and use-specific regulations and to ensure compliance with these regulations.

Subject to the exclusions and limitations set out below the Information contained in this publication or as otherwise supplied to the User is believed to be accurate and has been given in good faith. It is for the User to use the Information contained in this publication or as otherwise supplied to the User with care and satisfy itself of the suitability of the product for their intended use and the applicability of the advice given. Except to the extent that exclusion is prevented by applicable law WHW Plastics Ltd gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded and accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Revision: CLP2

CENTRI-BASE HEAT CURE - POLY(MMA) BASED

Date: 13 -June-2023 Page: 6 / 6