Printing date 05.02.2018

Version number 4

Revision: 05.02.2018

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: MegaBase Adhesive
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- Application of the substance / the mixture Priming
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Dreve Dentamid GmbH Max-Planck-Straße 31 59423 Unna / Germany Tel.: ++49 2303 /8807-0 Fax.: ++49 2303 / 8807-55
- Further information obtainable from: Department Research & Development Fax: ++49 2303 / 8807-562 Email: sicherheitsdatenblatt@dreve.de
- **1.4 Emergency telephone number:** Tel.: ++ 49 211 / 797-3350 Plant Fire Department Henkel

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS07

Eye Irrit. 2H319Causes serious eye irritation.Skin Sens. 1H317May cause an allergic skin reaction.STOT SE 2H326May cause drawsinger or dispinance.

STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation. • Hazard pictograms



- · Signal word Danger
- Hazard-determining components of labelling: ethyl acetate methyl methacrylate

(Contd. on page 2)



Printing date 05.02.2018

Hazard statements

Version number 4

Trade name: MegaBase Adhesive

(Contd. of page 1)

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness. · Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition P210 sources. No smoking. P241 Use explosion-proof electrical/ventilating/lighting equipment. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/ international regulations. · 2.3 Other hazards · Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 141-78-6	ethyl acetate	50-100%
EINECS: 205-500-4	🚸 Flam. Liq. 2, H225; 🕂 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 80-62-6	methyl methacrylate	2.5-10%
EINECS: 201-297-1	♦ Flam. Liq. 2, H225; ♦ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
• Additional information: For the wording of the listed bazard phrases refer to section 16		

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor. • After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Do not induce vomiting.

Call a doctor immediately.

• 4.2 Most important symptoms and effects, both acute and delayed Nausea Dizziness

Headache

(Contd. on page 3)

GB



Revision: 05.02.2018

Printing date 05.02.2018

Version number 4

Trade name: MegaBase Adhesive

(Contd. of page 2)

- Vomitus
- 4.3 Indication of any immediate medical attention and special treatment needed If swallowed or in case of vomiting, danger of entering the lungs.
- If swallowed, gastric irrigation.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Avoid contact with skin and eyes. Ensure adequate ventilation Do not breathe vapour/spray. Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars. Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Avoid contact with skin and eyes.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- **Requirements to be met by storerooms and receptacles:** Protect from heat and direct sunlight.
- Store at max. 25°C.
- Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

G



Version number 4

Revision: 05.02.2018

Trade name: MegaBase Adhesive

Printing date 05.02.2018

· 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

141-78-6 ethyl acetate

WEL Short-term value: 400 ppm Long-term value: 200 ppm

80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
- **Respiratory protection:** Short term filter device: Filter A.
- · Protection of hands:



Protective gloves

Protective gloves should be changed regularly, especially after intensive contact with the product. For every workplace a suitable type of protective gloves must be selected.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

• Material of gloves

Butyl rubber (0,7 mm) EN 374

As there are many different conditions in every day work these indications can only serve as an aid to orientation for the selection of suitable gloves for the handling of chemical products. By no means they can replace qualifying examinations by the end-user.

These recommendations only apply to the product mentioned in the safety data sheet. When mixing with other substances or under conditions deviant from norm EN 374 a manufacturer of CE-approved gloves should be referred to.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Penetration time: > 120 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

GB



Printing date 05.02.2018

Version number 4

Revision: 05.02.2018

Trade name: MegaBase Adhesive

(Contd. of page 4) The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9.1 Information on basic physical and	chemical properties
General Information	
Appearance:	
Form:	Fluid
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	-90,5 °C
Initial boiling point and boiling range	e: 76 °C
Flash point:	-4 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	460 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation o explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	2,1 Vol %
Upper:	11,5 Vol %
Oxidising properties	Not determined
Vapour pressure at 20 °C:	97 hPa
Density at 20 °C:	0,90 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water at 20 °C:	0,05 g/l
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

— GB



Printing date 05.02.2018

Version number 4

Revision: 05.02.2018

(Contd. of page 5)

Trade name: MegaBase Adhesive

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No dangerous reactions if used according to specifications.
- 10.2 Chemical stability Stable if used according to specifications.
- · Thermal decomposition / conditions to be avoided:
- Protect from heat and direct sunlight.

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.
- **10.4 Conditions to avoid** No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- \cdot Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

(Contd. on page 7)



Version number 4

Revision: 05.02.2018

Trade name: MegaBase Adhesive

(Contd. of page 6)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Printing date 05.02.2018

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue

HP 3 Flammable

HP 4 Irritant - skin irritation and eye damage

HP 5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number · ADR, IMDG, IATA	UN1173	
 · 14.2 UN proper shipping name · ADR · IMDG, IATA 	1173 ETHYLACETAT, LÖSUNG ETHYL ACETATE, SOLUTION	
 · 14.3 Transport hazard class(es) · ADR, IMDG, IATA 		
· Class · Label · 14.4 Packing group	3 Flammable liquids. 3	
· ADR, IMDG, IATA	Ш	
 · 14.5 Environmental hazards: · Marine pollutant: 	No	
 · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category 	Warning: Flammable liquids. 33 F-E,S-D B	
 14.7 Transport in bulk according to Ann of Marpol and the IBC Code 	nex II Not applicable.	
· Transport/Additional information:		
 ADR Limited quantities (LQ) 	1L	
	(Contd. on page	



Printing date 05.02.2018

Version number 4

Revision: 05.02.2018

Trade name: MegaBase Adhesive

	(Contd. of page 7)
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2
 Transport category Tunnel restriction code 	Z D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1173 ETHYL ACETATE, 3, II

SECTION 15: Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

 Information about limitation of use: Employment restrictions concerning juveniles must be observed.

· Technical instructions (air):

Class	Share in %
NK	50-100

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- · Department issuing SDS: Department Research & Development
- · Contact: Dr. Thomas Veit, Lothar Sutor
- Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 (Contd. on page 0)

(Contd. on page 9)

GB



Printing date 05.02.2018

Version number 4

Revision: 05.02.2018

Trade name: MegaBase Adhesive

(Contd. of page 8)

ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 • * Data compared to the previous version altered.